



DARE TO DIY DIFFERENTLY

Liquid Rubber Color Sealant is a brush, roll-on and spray-able high-performance, acrylic, elastomeric coating that can be applied over many existing surfaces including concrete, wood, brick, metal... which forms a durable, flexible, seamless, colored membrane.

Liquid Rubber Color Sealant contains no solvents, is non-flammable and not affected by sunlight or occasional chemical spills.



LIQUID RUBBER COLOR SEALANT PERFORMANCE FEATURES

- Durable, Waterproof Surface
- Excellent Adhesion to Most Substrates
- No VOC's, Solvents or Harmful Odors
- Color Options Available
- Extreme Flexibility
- No Specialized Equipment Needed
- UV Resistant, Solar Reflective



APPLICATION EQUIPMENT

Liquid Rubber Color Sealant is applied using a brush, roller, or airless paint sprayer to provide a seamless and fully adhered membrane to most substrates. This highly flexible all-purpose sealant is designed as a stand-alone coating but can be applied over our **Liquid Rubber Multi-purpose Primer** for increased adhesion. **Liquid Rubber Color Sealant** should require around 2-3 heavy coats to achieve a 30 mil (0.76mm) (DFT) membrane.

• Flow Rate	6 gpm
• Pressure	500-2000 PSI

• Tip Size	0.519 – 0.527
• Motor	11 HP

The sprayer must be capable of spraying an elastomeric coating. BrookfieldCPs = 8-15000

+1 855-592-1049 | support@shopliquidrubber.com | shopliquidrubber.com



DRYING TIME

At 25°C and 50% relative humidity, **Liquid Rubber Color Sealant** fully cures in 24-48 hours. Curing time increases with thickness, in colder temperatures or higher humidity so environmental conditions must be considered before application.



SUITABLE APPLICATIONS INCLUDE BUT ARE NOT LIMITED TO

- Metal Roofs
- Concrete Roofs
- Basement Walls
- Walls & Ceilings



PHYSICAL PROPERTIES

Color (Liquid)	Various
% Solids (v/v) (Liquid)	48-52%
Tensile Strength	>180 psi
Elongation	>1500%
Low Temp Flex	-7°C

Water Absorption (EN 1062)	.0007 kg/m ² hr 0.5
Permeance (ASTM E96-A)	0.1793 Perms @ 60 mil.
Adhesion to Steel	>29 psi
Working Temp Range	-40°C/150°C
Hardness	20 - 25 (Shore A)

LIMITATIONS & WARRANTY

- Do not apply to dirty or contaminated surfaces
- Do not apply below 10°C/50°F
- Avoid contact with solvents and solvent type adhesives
- Product will remain tacky after it cures, not meant for decks, patios, floors or walking surfaces
- Do not apply over coal tar

PACKAGING

- 1000 L (264 Gal) IBC Tote
- 205 L (55 Gal.) Plastic Drum
- 18.9 L (5 Gal.) Pails
- 3.78 L (1 Gal.) Cans

+1 855-592-1049 | support@shopliquidrubber.com | shopliquidrubber.com