



DARE TO DIY DIFFERENTLY

Liquid Rubber Multi-Purpose Primer is a high performance, engineered bonding aid designed to improve the adhesion of Liquid Rubber membranes and minimize moisture vapor drive over a variety of substrates.

Liquid Rubber Multi-Purpose Primer is a single component clear primer, suitable for easy and safe application to numerous surfaces including concrete, wood, fiberglass, metal, and cures into a hard, clear film.



LIQUID RUBBER MULTI-PURPOSE PRIMER PERFORMANCE FEATURES

- Reduces Moisture Vapor Drive
- Dries to a Hard, Clear Finish
- Dries Quickly
- Increases Adhesion of Coatings
- Excellent Adhesion to Most Substrates
- Hybrid Formulation



APPLICATION EQUIPMENT

Liquid Rubber Multi-Purpose Primer is applied either by brush, roller, or airless spray application. This primer will require one to two coats depending on the absorbent nature of the substrate, with the goal of minimizing vapor drive and maximizing adhesion of the waterproof membrane. The recommended coating thickness of the Multi-Purpose Primer is between 4-5 mils DFT (.01 mm) (175-200 ft²/gal). For best results, primer should be applied to a dry surface that is free of dirt, dust, debris, oil, grease, silicone, laitance, efflorescence, or any other contaminants that would prevent adhesion. Application within 24 hours of rain is not recommended.

Can be sprayed using a light industrial paint sprayer suitable for primers. 0.515-0.519 spray tip.

+1 855-592-1049 | support@shopliquidrubber.com | shopliquidrubber.com

The information contained herein is the best available to Liquid Rubber Canada Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Canada Inc. assumes no liability for any damages incurred in association with the use of Liquid Rubber Canada Inc. products. Information is subject to change without notice.



DRYING TIME

Curing time will vary depending on temperature and relative humidity. **Liquid Rubber Multi-Purpose Primer** will be dry to the touch and will be ready for coating within 1-2 hours at 25°C (50% RH). Apply topcoat as soon as possible after it has dried to the touch and is uniform in color.



SUITABLE APPLICATIONS INCLUDE BUT ARE NOT LIMITED TO

- Wood
- Concrete
- Fiberglass
- Other coatings (test)
- Metal
- PVC



PHYSICAL PROPERTIES

Color (Liquid)	Clear
Viscosity	50 CPs
Solids	>40%

Adhesion to Wood	Cohesive Failure
Adhesion to Concrete	Cohesive Failure
Adhesion to Steel	Cohesive Failure

LIMITATIONS & WARRANTY

- Do not apply to dirty or contaminated surfaces
- Do not apply below 10°C/50°F
- Avoid contact with solvents and solvent type adhesives
- Not for long-term UV exposure
- Do not apply over coal tar

PACKAGING

- 18.9 L (5 Gal.) Pails
- 3.78 L (1 Gal.) Cans
- 946 ml (1 Quart) Cans

+1 855-592-1049 | support@shopliquidrubber.com | shopliquidrubber.com