



DARE TO DIY DIFFERENTLY

Liquid Rubber Seam Tape is a peel and stick product designed to accept Liquid Rubber coatings onto its polyester backing. A 100% solids formulation of synthetic resins, thermoplastics, and non-curing rubber with a built-in primer.

Liquid Rubber Seam Tape makes the surface watertight prior to the applying of the coating, creating a superior method of waterproofing over conventional 3 course applications as well as eliminating dependence on the roof coating as the only water barrier.



LIQUID RUBBER SEAM TAPE PERFORMANCE FEATURES

- Exceptional Adhesion
- Remains Flexible to -35°C
- Conforms to Odd Shaped Surfaces
- Bonds to Virtually Any Surface
- Quick & Easy Application
- Will Not Harden



APPLICATION EQUIPMENT

Liquid Rubber Seam Tape is applied using hands, and tweezers to remove the backing film. Prepare the surface by cleaning and drying, ensuring it's free from dust, dirt, oils, flaking, salts, silicone, and other contaminants which may affect adhesion. Install Seam Tape directly over repair area by rolling or rubbing onto area to activate the bonding process. Adhesion begins immediately. Seam Tape is not UV stable and must be coated with a Liquid Rubber Sealant to prevent deterioration.

+1 855-592-1049 | support@shopliquidrubber.com | shopliquidrubber.com

The information contained herein is the best available to Liquid Rubber Canada Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Canada Inc. assumes no liability for any damages incurred in association with the use of Liquid Rubber Canada Inc. products. Information is subject to change without notice.



Versatility

Bonds to a wide range of surfaces including difficult roof materials such as EPDM, TPO, CSPE/Hypalon, most PVC, CPE, SBS, Asphalt BURs, plus all metal roofs, tiles, shingle, aluminum, galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry, OSB, etc.

Note – Does not stick to silicone.



SUITABLE APPLICATIONS INCLUDE BUT ARE NOT LIMITED TO

- RV Roofs & Mobile Homes
- Flat & Sloped Roofs
- Gutters & Flashing
- Ponds
- AC Units, Skylights & Vents
- Vinyl



PHYSICAL PROPERTIES

Color (Liquid)	Grey
Application Temp	-30°C to 65°C
Flexible Temp Range	-50°C to +90°C
Elongation	500%

Water Vapor Test (ASTM E 96 B)	.005g/100 ft ² / 24 hrs
Adhesion	19 psi/in width
Low Temperature Flex	½ inch radius at -35°C
Total Thickness	30 mils (1 MM)

LIMITATIONS & WARRANTY

- Must be applied to a clean dry surface
- Does not bond to silicone

PACKAGING

- 2-inch x 50 ft Roll
- 4-inch x 50 ft Roll

+1 855-592-1049 | support@shopliquidrubber.com | shopliquidrubber.com