



DARE TO DIY DIFFERENTLY

Liquid Rubber Seam Tape is a peel and stick product designed to accept Liquid Rubber coatings onto its polyester backing. A 100% solids formulation of synthetic resins, thermoplastics, and non-curing rubber with a built-in primer.

Liquid Rubber Seam Tape makes the surface watertight prior to the applying of the coating, creating a superior method of waterproofing over conventional 3 course applications as well as eliminating dependence on the roof coating as the only water barrier.



LIQUID RUBBER SEAM TAPE PERFORMANCE

FEATURES

- Exceptional Adhesion
- Conforms to Odd Shaped Surfaces
- Quick & Easy Application
- Remains Flexible to -35°C
- Bonds to Virtually Any Surface
- Will Not Harden



APPLICATION EQUIPMENT

Liquid Rubber Seam Tape is applied using hands, and tweezers to remove the backing film. Prepare the surface by cleaning and drying, ensuring it's free from dust, dirt, oils, flaking, salts, silicone, and other contaminants which may affect adhesion. Install Seam Tape directly over repair area by rolling or rubbing onto area to activate the bonding process. Adhesion begins immediately. Seam Tape is not UV stable and must be coated with a Liquid Rubber Sealant to prevent deterioration.



Versatility

Bonds to a wide range of surfaces including difficult roof materials such as EPDM, TPO, CSPE/Hypalon, most PVC, CPE, SBS, Asphalt BURs, plus all metal roofs, tiles, shingle, aluminum, galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry, OSB, etc.

Note – Does not stick to silicone.



SUITABLE APPLICATIONS INCLUDE BUT ARE NOT LIMITED TO

- RV Roofs & Mobile Homes
 - Flat & Sloped Roofs
 - Gutters & Flashing
 - Ponds
 - AC Units, Skylights & Vents
 - Vinyl
-



PHYSICAL PROPERTIES

Color (Liquid)	Grey
Application Temp	-30°C to 65°C
Flexible Temp Range	-50°C to +90°C
Elongation	500%

Water Vapor Test (ASTM E 96 B)	.005g/100 ft ² / 24 hrs
Adhesion	19 psi/in width
Low Temperature Flex	½ inch radius at -35°C
Total Thickness	30 mils (1 MM)

LIMITATIONS & WARRANTY

- Must be applied to a clean dry surface
- Does not bond to silicone

PACKAGING

- 2-inch x 50 ft Roll
- 4-inch x 50 ft Roll